

IPC270 IP66/IP69K Series

7inch~43inch IP66/IP69K Waterproof Panel PC with Intel Chipset



Key Features

- ◆ 7"~43" TFT LCD display with LED backlight
- ◆ IP66, IP69K Grade Waterproof
- ◆ 10 Points Capacitive 6H
- ◆ 350nits Brightness, Upgradable to 1000nits
- ◆ Rich Expansion: 3G/4G, WIFI, Blooth, RS232/RS422/RS485, GPIO Options
- ◆ Embedded, Wall Mounted, Vesa

System Parameters

Processor&Chipset	<ul style="list-style-type: none"> ● Intel® Processor ● Onboard Intel® i3,i5,i7, 4th~9th Generation
Memory	1 x DDR3 /DDR4 SO-DIMM socket, 2GB/4GB/8GB/16GB
Storage	1 x 2.5" SATA 500GB/1TB/2TB 1 x Msata 16GB/32GB/64GB/128GB/256GB
Cooling System	Fanless design
BIOS	AMI 16MB DPI Flash
Watchdog Timer	255 level, 0~255 sec
LAN	1 x Realtek RT8111E, 10/100/1000M, Support PXE, Wake on Lan
Audio	Realtek ACL662 Audio controller, Line-out, Mic-in.
Expansion Port	2 x MINI PCI-E full slot, 1 x SIM
OS	Linux/ Windows XP/7/8/10/11

Expansion Function

GPIO	Optional
3G/4G	Optional
WIFI/BT	Optional(802.11 a/b/g/n, Bluetooth 4.0)
RS422/485	Optional
Speaker	Optional

Degree of protection

IP66/IP69K	Default
------------	---------

Display Parameters

LCD Size	27" TFT (LED Backlight)
Resolution	1920*1080
Brightness	300cd/m ² (1000cd/m ² optional)
Aspect ratio	16:9
Life Time	50,000hrs

Contrast Ratio	(1200:1)
Response Time	3.5ms
Viewing Angle	170/160(U/D), 178/170(L/R)
Color Resolution	16.7M

Touch Screen Parameters

Touch Type	10 Points Capacitive Touch
Surface Hardness	6H>(Capacitive Touch)
Touch Validity:	>1,000,000
Resolution	4096*4096
Life Time	50,000hrs
Transparent Rate	>85%

IO Interface

COM	2x COM(Default RS232, 6 maximum)
RS422/485	Optional (1x RS485/422)
USB	2 x USB2.0
LAN	1 x RJ45, 10/100/1000M (2LAN Optional)

Power Supply

Power Supply	12V DC Power Input
Power Consumption	<90W
Wide Voltage	Optional (DC 6~36V Wide Voltage, IPTS)

Installation

VESA	100mm*100mm
Embedded	Cabinet Hole Size: 635mm*373mm

Environments

Operating Temp	-10°C~50°C
Storage Temp	-30°C~70°C
Relative Humidity	5~95%@10°C (Non-condensing)
Vibration	5~500Hz,1.5G,0.15mm peak value
Shake	1.5 Grms, IEC 60068-2-64, 5 ~ 500 Hz, 1 hr/axis
Shock	10 Grms, IEC 60068-2-64, Half sine wave,for 11 ms
EMC	CE/FCC Class A

Enclosure

Housing Material	Aluminum Chassis with fanless design
Dimensions	645 mm (W) x 383 mm (D) x 77mm (H)
Net Weight	9.2KG